## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

Claim 1 (currently amended): An apparatus comprising:

a plurality of sets of interleaved air bags collectively forming a patient supporting surface, each set of interleaved air bags being independently inflatable; and

a high air pressure source in fluid communication with the air bags; wherein the high air pressure source is operable to alternately inflate the sets of interleaved air bags to periodically relieve alternate regions of the patient's body from pressure;

a framework of inflatable tubes:

a patient-enclosing air tent mounted on the framework of inflatable tubes, the inflatable tubes being operable, when inflated, to support the air tent above the patient, wherein the patient enclosing air tent is sized to enclose at least a portion of a single patient except a head portion of the patient;

an air inlet connected to an air-cooling system for introducing cooled air into the patient enclosing air tent; and

an outlet connected to the air-cooling system for re-circulating air from the air tent back to the air-cooling system to conserve energy.

Claim 2 (canceled)

Claim 3 (currently amended): The apparatus of claim [[2]] 1, further comprising a coaxial hose having an inner passage to send air into the air tent and an outer coaxial passage to carry air from the air tent.

## Claim 4 (canceled)

Claim 5 (currently amended): The apparatus of claim [[4]] 1, further comprising a fluid connection between the air bags and the air cooling system, wherein the air bags are operable to be pressurized with either relatively high flow cold air which assists in cooling the patient but provides relatively little support or with relatively high pressure air which is sufficient to support the patient but which provides relatively less cooling effect.

Claim 6 (currently amended): <del>The apparatus of claim 1, further</del> <u>An apparatus</u> comprising:

- a plurality of air bags collectively forming a patient supporting surface;
- a high air pressure source in fluid communication with the air bags;

a fluid connection between the air bags and the air cooling system, wherein the air bags can be pressurized with either relatively high flow cold air which assists in cooling the patient but provides relatively little support or with relatively high pressure air which is sufficient to support the patient but which provides relatively less cooling effect;

a framework of inflatable tubes;

a patient-enclosing air tent mounted on the framework of inflatable tubes, the inflatable tubes being operable, when inflated, to support the air tent above the patient, wherein the patient enclosing air tent is sized to enclose at least a portion of a single patient except a head portion of the patient:

an air inlet connected to an air-cooling system for introducing cooled air into the patient enclosing air tent; and

an outlet connected to the air-cooling system for re-circulating air from the air tent back to the air-cooling system to conserve energy.

Claim 7 (currently amended): The apparatus of claim [[1]] 6, further comprising at least one aperture on the air tent for removable conduits, the aperture comprising a sleeve of flexible material operable to be tightened around a conduit by twisting the sleeve so that it collapses radially about the conduit.

Claim 8 (original): The apparatus of claim 7, wherein when no conduit is present, the sleeve is operable to be twisted tightly enough to close the aperture completely.

Claim 9 (currently amended): The apparatus of claim [[1]] 6, wherein the framework of inflatable tubes are operable to be moved between a closed position extending over the patient and an open position extending away from the patient, the framework including one or more inflatable connectors to releasably secure the framework in the closed position.

Claim 10 (currently amended): The apparatus of claim [[9]] 1, wherein the framework of inflatable tubes has a longitudinal dimension, wherein the framework of inflatable tubes is split along the longitudinal dimension between left and right halves, where each half can be moved from the closed position to the open position.

Claim 11 (currently amended): The apparatus of claim [[10]] 9, wherein at least one aperture is provided in the framework of inflatable tubes for receiving the inflatable connector.

Claim 12 (original): The apparatus of claim 11, wherein the inflatable connector comprises a stem and an inflatable protuberance having an outer dimension that, when the inflatable protuberance is inflated, exceeds the diameter of the aperture.

Claim 13 (original): The apparatus of claim 12, wherein the inflatable connector further comprises a tab attached to the protuberance to facilitate insertion of the protuberance through the aperture.

Claim 14 (previously presented): An apparatus comprising:

- a pressurized air source;
- a framework of inflatable tubes in fluid connection with the pressurized air source, the framework of inflatable tubes being split between left and right halves along a longitudinal dimension of the framework, each half further comprising an upper body section and a lower body section; each section of each half being independently operable to be moved between a closed position extending over the patient and an open position extending away from the patient;

a patient-enclosing air tent mounted on the framework of inflatable tubes, the inflatable tubes being operable, when inflated, to support the air tent above the patient;

an air-cooling system to provide cold air to the interior of the patientenclosing air tent, the cold air to affect a core temperature of the patient; and an outlet connected to the air-cooling system for re-circulating air from the air tent back to the air-cooling system to conserve energy.

Claim 15 (original): The apparatus of claim 14, the patient-enclosing air tent having a plurality of transparent windows to enable visual contact between the patient and another person exterior of the patient-enclosing air tent.

Claim 16 (canceled)

Claim 17 (currently amended): The apparatus of claim [[16]] 14, the framework including:

at least one inflatable connector to releasably secure the left and right halves of the upper body section together; and

at least one additional inflatable connector to releasably secure the left and right halves of the lower body section together.

Claim 18 (previously presented): The apparatus of claim 17, the framework further including:

at least one corresponding aperture in the upper body section of the framework for receiving the at least one inflatable connector; and

at least one additional corresponding aperture in the lower body section of the framework for receiving the at least one additional inflatable connector.

Claim 19 (previously presented): The apparatus of claim 18, wherein the inflatable connectors each comprise a stem and an inflatable protuberance having an outer dimension that, when the inflatable protuberance is inflated, exceeds the diameter of the corresponding aperture.

Claim 20 (previously presented): The apparatus of claim 19, wherein the inflatable connector further comprises a tab attached to the protuberance to facilitate insertion of the protuberance through the corresponding aperture.

Claim 21 (previously presented): An apparatus comprising:

- a plurality of air bags collectively forming a patient supporting surface;
- a high-pressure air source in fluid connection with the air bags, the high-pressure air source operable to provide sufficient air pressure to support the patient;
- a framework of inflatable tubes also in fluid connection with the highpressure air source;
- a patient-enclosing air tent mounted on the framework of inflatable tubes, the inflatable tubes being operable, when inflated, to support the air tent above the patient; and

an air-cooling system to provide cold air to the interior of the patientenclosing air tent, the cold air to affect a core temperature of the patient.

Claim 22 (canceled)

Claim 23 (canceled)

Claim 24 (new): The apparatus of claim 21, wherein at least one aperture is provided in the framework of inflatable tubes for receiving the inflatable connector.

Claim 25 (new): The apparatus of claim 21, including an outlet connected to the air-cooling system for re-circulating air from the air tent back to the air-cooling system to conserve energy.